



11671.1

STL 950/20/5,00-H-G GN

STL 950/20/5,00-H-G GN



Male pin block, No. of poles: 20, Width: 100 mm, Colour: Green

## Business data

Connector version	Attached plug-in connector
Packaging unit	50
Quantity unit	PC
Packaging type	Carton
Type of banding	Without
Weight per piece (not including packaging)	6.58
Weight per piece (including packaging)	7.58
Unit of weight	G
Customs number	85366930
Country of origin	QU

**11671.1**

**STL 950/20/5,00-H-G GN**

**STL 950/20/5,00-H-G GN**

## Technical Data

---

### Dimensions

---

Length	12 mm
Length of the pin	3.5 mm
Width	100 mm
Width left	2.5 mm
Width right	2.5 mm
Height	8.4 mm
Drill hole diameter	1.4 mm
Diameter of connecting pin	1 mm
Pitch	5 mm

### Ratings

---

Rated voltage	250 V
Rated current	12 A
Rated impulse voltage	4 kV
Overvoltage category	III
Contamination degree	3

**11671.1**

**STL 950/20/5,00-H-G GN**

**STL 950/20/5,00-H-G GN**

## Technical Data

---

### Connection data

---

Angle of PCB/contact	0°/180° (horizontal)
Number of plug-in rows	1
No. of poles	20

### Materials

---

Insulation housing	Polyamide 6.6
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	105 °C
Contact pin	Copper alloy

**11671.1**

**STL 950/20/5,00-H-G GN**

**STL 950/20/5,00-H-G GN**

## Technical Data

---

### Further technical data

---

Storage temperature, min.	-40 °C
Storage temperature, max.	105 °C
Insulation resistance	1*10 <sup>13</sup> Ohm x cm
Creepage-current resistance	CTI 600
Glow wire flammability index GWFI	GWFI 850
GWFI after-glow time	30 Sek.
Glow wire ignition temperature GWIT	GWIT 775 °C
GWIT exposure time	5 Sek.
Plug-in cycles acc. to standard	100
Recommended wave soldering temperature	265 °C
Recommended wave soldering duration, min.	3 Sek.
Recommended wave soldering duration, max.	4 Sek.

11671.1

STL 950/20/5,00-H-G GN

STL 950/20/5,00-H-G GN

## Approvals

---

### cUL Recognized

---

cUL Recognized	CSA 22.2 No.158
cUL Recognized	✓
cUL Usegroup B: rated voltage	300 V
cUL Usegroup B: rated current	15 A
cUL Usegroup C: rated voltage	150 V
cUL Usegroup C: rated current	15 A
cUL Usegroup D: rated voltage	300 V
cUL Usegroup D: rated current	10 A
cUL wire material	Cu

### UL Recognized

---

UL Recognized	UL 1059
UL Recognized granted	✓
UL Usegroup B: rated voltage	300 V
UL Usegroup B: rated current	15 A
UL Usegroup C: rated voltage	150 V
UL Usegroup C: rated current	15 A
UL Usegroup D: rated voltage	300 V
UL Usegroup D: rated current	10 A

11671.1

STL 950/20/5,00-H-G GN

STL 950/20/5,00-H-G GN

## Approvals

---

### UL Recognized

---

UL wire material	Cu
UL factory wiring	✓

### VDE approval

---

VDE approval	DIN EN 61984
VDE approval granted	✓
VDE rated voltage	250 V
VDE rated current	12 A
VDE rated impulse voltage	4 kV
VDE overvoltage category	III
VDE contamination degree	3

11671.1

STL 950/20/5,00-H-G GN

STL 950/20/5,00-H-G GN

Media

---

