



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 36.5              |
| B1  | 14.3              |
| B2  | -                 |
| C   | 68                |

| NO. | BESCHREIBUNG / DESCRIPTION           |
|-----|--------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN  |
| 3   | DICHTKÖRPER / GROMMET                |
| 4   | ENDRING / ENDRING                    |
| 5   | KONTAKTSTIFT / CONTACT PIN           |
| 7   | ZYLINDERGHÄUSE / BARREL              |
| 9   | ÜBERWURFMUTTER / COUPLING NUT        |
| 10  | DICHTRING FRONT / FRONT SEALING RING |
| 12  | ENDGEHÄUSE / ENDBELL                 |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.

Specification and Dimensions subject to change  
Drawings illustrate normal insulator positioning

|                         |                 |
|-------------------------|-----------------|
| Material Specification: |                 |
| Shell Material:         | Aluminium alloy |
| Shell Plating:          | Nickel plated   |
| Insulator Material:     | CR-Elastomere   |
| Contact Material:       | Copper alloy    |
| Contact Plating:        | Hard silver     |

all dimensions are in mm  
Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
CUSTOMER



description CA3106E18-4PYB-A34  
Plug, straight  
Endbell with clamp and bushing  
Solder Cup / Pin / Layout: 18-4

© All rights reserved. Reproduction or issue to third in any form  
whenever is only permitted with written authorization of ITT Cannon

page 1/1  
revision 1840 30. Apr 20