
C330C223K5R5HA7303

Capacitor, ceramic, 0.022 uF, +/-10% Tol, 50V, X7R, Lead Spacing=0.2"



Dimensions (in)

ID	Dimension	Tolerance
L	0.3	max
H	0.36	max
T	0.15	max
S	0.2	+/-0.03
LL	0.276	min
F	0.02	+0.004/-0.001
K	0.02	

Specifications

Manufacturer:	KEMET
Capacitance:	0.022 uF
Lead Spacing:	0.2"
Voltage:	50V
Temperature Coefficient:	X7R
Tolerance:	+/-10%
Body Type:	Radial Conformal
Lead Type:	Standard Leads
Lead Form:	Straight Leads
Termination Type:	Tin-Lead (SnPb)
Package Kind:	T&R
Package Size:	12in
Package Type:	Type 2
Package Quantity:	1500

Notes:
-Lead length shown is for parts supplied in bulk. See packaging specifications for lead lengths when not provided in bulk

IntelliData

© 2006-2012 IntelliData.net

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.