www.lemo.com

CAB.810.GLA.C921GZ

SUMMARY

Wires

Low voltage	**10**
Coax	**1**



Image is for illustrative purpose only

Series	2P
Termination type	Male crimp mixed / multi coax
IP rating	50
AWG wire size	22.00 - 22.00
Cable Ø	7.30 - 9.20 mm
Status	active
Matching parts	CLB.810.GLL1G

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model	CA*: Straight plug with cable collet and nut for fitting a bend relief
Keying	3 keys (alpha=0, gamma=60; Plug: male contacts; Receptacle: female contacts)
Housing Material	PSU (Polysulfone), grey
Weight	10.07 g

Performance

Configuration	2P.810 : 1 Coax (50 Ohm), 10 Low V.
Insulator	L: PEEK for solder contacts
Rated Current	5 Amps

Specifications

Test voltage (kV rms) Contact-contact: 1.25
Air clerance min.: 0.9 mm
Creepage distance min.: 0.9 mm


Others


Endurance (Shell): >1000 mating cycles


LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

DRAWINGS

Draws







Dimensions

	A	L
mm.	18	57
in.	0.71	2.24

RECOMMENDED BY LEMO

Tools

Cables

LEMO products and services are provided “as is”. LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.