GCJ188L81E823MA01#

Note: This datasheet may be out of date

Please download the latest datasheet of GCJ188L81E823MA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=GCJ188L81E823MA01%23

"#" indicates a package specification code.


















< List of part numbers with package codes > GCJ188L81E823MA01J GCJ188L81E823MA01D



Appearance & Shape







References

Packaging	Specifications	Standard
		Packing
		Quantity
J	330mm Paper Tape	10000
D	180mm Paper Tape	4000

Mass (typ.)		
1 piece	6.3mg	
φ180mm Reel	144g	



Resin external electrode products

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



1 of 2

GCJ188L81E823MA01#

Note: This datasheet may be out of date.

Please download the latest datasheet of GCJ188L81E823MA01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=GCJ188L81E823MA01%23

"#" indicates a package specification code.

Specifications

Length	1.6±0.2mm
Width	0.8±0.1mm
Thickness	0.8±0.1mm
Capacitance	82000pF ±20%
Distance between external terminals g	0.5mm min.
External terminal size e	0.2 to 0.5mm
Operating Temperature Range	-55°C to 150°C
Rated Voltage	25Vdc
Size code in inch(mm)	0603 (1608M)
Capacitance change rate	+15.0/-40.0%
Temperature characteristics (complied standard)	X8L(MURATA)
Temperature range of temperature characteristics	-55°C to 150°C

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

