


SIB-120-02-F-S



SIR1-15-L-S-A

(2.54 mm) .100"

SIB, SIR1 SERIES

ONE-PIECE INTERFACES

SPECIFICATIONS

Insulator Material:
Black Liquid Crystal Polymer
Contact Material:
Phosphor Bronze
Plating:
Au or Sn over
50 μ" (1.27 μm) Ni
Current Rating:
2.6 A per pin
(1 pin powered)
Operating Temp Range:
-55 °C to +125 °C
RoHS Compliant: Yes

PROCESSING

Lead-Free Solderable: Yes
SMT Lead Coplanarity:
(0.10 mm) .004" max (02-19)
(0.15 mm) .005" max (20-30)

RECOGNITIONS



SIB	1	NO. OF POSITIONS	02	PLATING OPTION	S	OPTION
02 thru 30 (Per Row)			-F = Gold flash on contact, Matte Tin on tail		-LC = Locking Clip (Manual placement required)	

Note: The SIB Series is intended for vertical mating only.

Note: Some sizes, styles and options are non-standard, non-returnable.

SPECIFICATIONS

Insulator Material:
Black LCP
Contact Material:
Phosphor Bronze
Plating:
Au or Sn over
50 μ" (1.27 μm) Ni
Current Rating:
2.8 A per pin
(1 pin powered)
Weld Tab:
Phosphor Bronze
RoHS Compliant:
Yes

PROCESSING

Lead-Free Solderable:
Yes
SMT Lead Coplanarity:
(0.10 mm) .004" max

RECOGNITIONS



SIR1	NO. OF POSITIONS	PLATING OPTION	S	OPTION
-03, -05, -10, -15 (Per Row)		-L = 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail		-A = Alignment Pin -K = (4.00 mm) .157" DIA Polyimide Film Pick & Place Pad -TR = Tape & Reel
		-S = 30 μ" (0.76 μm) Gold on contact, Matte Tin on tail		

Note: Some sizes, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.TOBY.CO.UK

All parts within this catalog are built to Samtec's specifications.
Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.