





Surface
SMT
Mount

.050" BOARD STACKER FW SERIES


FW-25-03-G-D-163-120



FW-20-05-G-D-500-075



FW-10-05-G-D-400-090-A



SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?FW

Insulator Material:

Black Liquid

Crystal Polymer

Terminal Material:

Phosphor Bronze

Plating:

Sn or Au over 50µ" (1,27µm) Ni

Current Rating:

1.75A @ 80°C ambient

Operating Temp Range:

-55°C to +125°C

RoHS Compliant:

Yes

Processing:

Max Processing Temp:

230°C for 60 seconds, or

260°C for 20 seconds 3x

Lead-Free Solderable:

Yes

SMT Lead Coplanarity:


(0,10mm) .004" max (02-30)

(0,15mm) .006" max (31-50)



Mates with:
CLP, FFSD, FLE

APPLICATIONS



Lead Style	FW	CLP	Mated Height
FW-XX-03-X-X-233-065		-02	(8,13) .320
FW-XX-03-X-X-303-065			(9,91) .390

Low profile or
skyscraper styles

(1,27mm x 1,27mm)
.050" x .050"
micro pitch

Variable
board spacing

Surface
mount

FW	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	D	STACKER HEIGHT	POST HEIGHT	OPTION
	02 thru 50	Specify LEAD STYLE from chart	-G = 10µ" (0,25µm) Gold on post, Gold flash on tail -L = 10µ" (0,25µm) Gold on post, Matte Tin on tail -F = Gold flash on post, Matte Tin on tail		-“XXX” = Stacker Height (in inches) Example: -250 = (6,35mm) .250"	-“XXX” = Post Height (in inches) (1,65mm) .065" minimum Example: -065 = (1,65mm) .065"	-ES = End Shroud (-075 post height only. Mate only with CLP.) (5,46mm) .215" to (15,49mm) .610" stacker height only 9 pins/row min. -EP = End Shroud with Guide Post (-075 post height only. Mate only with CLP.) (5,46mm) .215" to (15,49mm) .610" stacker height only 9 pins/row min. -A = Alignment Pin (3 positions min.) (5,46mm) .215" to (15,75mm) .620" stacker height only -P = Pick & Place Pad (5 positions min.) -TR = Tape & Reel (Post+Stacker Height = (17,46mm) .6875 max.)

LEAD STYLE	STACKER HEIGHT	STACKER + POST
-03	(5,46) .215 to .335	(7,11) .280 to .400
-05	(8,64) .340 to .610	(10,29) .405 to .675

TAPE & REEL AVAILABILITY

No tooling charges.
Minimum order is the lesser of
a full reel quantity or 125 pieces.
Order any quantity above minimum.
In-house design, manufacture.
Quick turn-around.

Call Samtec for specifications
and ordering information.

Note: This Series is
non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047

SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299

SAMTEC NORDIC/BALTIC • Tel: +46-84477280 • Fax: +46-87420413

SAMTEC JAPAN • Tel: 045-475-1385 • Fax: 045-475-1340

SAMTEC HONG KONG • Tel: 852-26904858 • Fax: 852-26904842

SAMTEC KOREA • Tel: 82-31-717-5685 • Fax: 82-31-717-5681

SAMTEC SILICON VALLEY • Tel: 408-395-5900 • Fax: 408-395-1520

SAMTEC FRANCE • Tel: 33 01 60 95 06 60 • Fax: 33 01 60 95 06 61

SAMTEC ISRAEL • Tel: 972-3-7526600 • Fax: 972-3-7526690

SAMTEC CHINA • Tel: 86-21-61103766 • Fax: 86-21-61103766

SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112 • Fax: 27 86 6714432

SAMTEC UK • Tel: 44 01236 739292 • Fax: 44 01236 727113

SAMTEC ITALY • Tel: 39 039 6890337 • Fax: 39 039 6890315

SAMTEC INDIA • Tel: +91-80-3272 1612 • Fax: +91-80-4152 8187

SAMTEC TAIWAN • Tel: 886-2-2735-6109 • Fax: 886-2-2735-5036

SAMTEC ANZ • Tel: 613 9512 7747 • Fax: 613 9512 7745