




Contact Layout



| Contacts<br>(Insert arrangement 23-32) |              |              |                     |             |             |
|--|--------------|--------------|---------------------|-------------|-------------|
| Contact position ID                    | Location     |              | Contact position ID | Location    |             |
|  | X-axis (mm)  | Y-axis (mm)  |                     | X-axis (mm) | Y-axis (mm) |
| A                                      | +100 (2.54)  | +450 (11.43) | T                   | +325 (8.26) | +025 (0.64) |
| B                                      | +325 (8.26)  | +325 (8.26)  | U                   | +300 (7.62) | -125 (3.18) |
| C                                      | +425 (10.80) | +150 (3.81)  | V                   | +200 (5.08) | -250 (6.35) |
| D                                      | +450 (11.43) | -075 (1.91)  | W                   | +000 (0.00) | -300 (7.62) |
| E                                      | -375 (9.53)  | -275 (6.99)  | X                   | -200 (5.08) | -260 (6.35) |
| F                                      | +200 (5.08)  | -400 (10.16) | Y                   | -300 (7.62) | -125 (3.18) |
| G                                      | +000 (0.00)  | -450 (11.43) | Z                   | -325 (8.26) | +025 (0.64) |
| H                                      | -200 (5.08)  | -400 (10.16) | a                   | -250 (6.35) | +175 (4.45) |
| J                                      | -375 (9.53)  | -275 (6.99)  | b                   | -150 (3.81) | +300 (7.62) |
| K                                      | -450 (11.43) | -075 (1.91)  | c                   | +100 (2.54) | +150 (3.81) |
| L                                      | -425 (10.80) | +150 (3.81)  | d                   | +150 (3.81) | +000 (0.00) |
| M                                      | -325 (8.26)  | +325 (8.26)  | e                   | +075 (1.91) | -150 (3.81) |
| N                                      | -100 (2.54)  | +450 (11.43) | f                   | -075 (1.91) | -150 (3.81) |
| P                                      | +000 (0.00)  | +325 (8.26)  | g                   | -150 (3.81) | +000 (0.00) |
| R                                      | +150 (3.81)  | +300 (7.62)  | h                   | -100 (2.54) | +150 (3.81) |
| S                                      | +250 (6.35)  | +175 (4.45)  | j                   | +000 (0.00) | +000 (0.00) |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 23         | -32             | 32                 | 20            | I              | All              | MS20056-32 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

PN: 8D523S32SA

|                |                                       |                            |   |
|----------------|---------------------------------------|----------------------------|---|
| A              | 07-10-2016                            | First Release              |   |
| ISS            | DATE                                  | Latest modification - by   | MOD N°  |
| Designed By:   |                                       | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Stainless Steel Plug 8D series</b> |                            |   |
| SCALE          |                                       | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                       | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>                |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D523S32SA-C</b>    |                            | SHEET 2/2   |